


K40S

GEARBOXES

K40S

Worm & Wheel Reduction Gearbox

Molded Housings, Solid Shaft Output, **3:5:1 - 60:1**



Solid Shaft Output	Ratio	Input RPM	Output RPM	Output Torque	
				inch-LBS	Nm
K40S-3.5	3:5:1	1800	514.3	102	11.6
K40S-10	10:1	1800	180	102	11.6
K40S-15	15:1	1800	120	102	11.6
K40S-20	20:1	1800	90	105	11.9
K40S-30	30:1	1800	60	120	13.6
K40S-40	40:1	1800	45	112	12.7
K40S-48	48:1	1800	37.5	96	10.9
K40S-60	60:1	1800	30	75	8.5

Materials

Housing: Compression-molded glass filled Polyester

Worm: Ground steel worm

Wheel: Bronze, precision hobbled

Modifications and custom designed gearboxes available. Customizing such as Stainless Steel shafting, longer shafts for input/output, and internal keyways on K40H output bores. Testing in your application is necessary. You will need to assess duty cycles and confirm suitability with your own calculations. All figures listed are to be used for guidance only.

Specifications

Size: 3-3/8"H x 3-7/8"W x 3"D

Weight: less than 20 ounces

Input: Dual shaft 0.312" diameter with flats, steel, 0.63" long

Output: 0.500" diameter shaft with flat, steel, 0.56" long

Bearings: Input/Output shafts supported by sintered bronze

bushings Mounting: 8 different positions of the mounting flanges

ondrives.us

1-888-260-7466
516-771-6444

sales@ondrivesus.com
www.ondrivesus.com

